



>> RP-1649RE 24-P 10M Ethernet Hub

Feature

- Complies with IEEE 802.3 10Base-5/2/T Standards
- Transmission Rate : 10Mbps
- Topology: Tree (backbone and star)
- Access Method: CSMA/CD
- Provides up-link port for cascading
- Plug-and-Play design, no software configuration is required
- Auto-detection for bad port partition and auto-recovering
- NE-2000 compatible
- LEDs (Link/Activity/Partition) for monitoring operation status
- 19" rack mount width
- With internal universal power supply
- FCC CLASS A, CE

Specification

Protocol	<ul style="list-style-type: none">• CSMA/CD
Topologies	<ul style="list-style-type: none">• Star, Bus
Data Transfer Rate	<ul style="list-style-type: none">• 10Mbps
Power Supply	<ul style="list-style-type: none">• Internal power supply 100~240VAC
Power consumption	<ul style="list-style-type: none">• 19 W
Environment	<ul style="list-style-type: none">• Operating Temperature: 0°C ~ 55°C• Operating Humidity: 10% ~ 90%
Dimension	<ul style="list-style-type: none">• 440 * 44 * 122 mm
Certification	<ul style="list-style-type: none">• FCC, CE

Ordering Information

RP-1649RE 24-P 10M Ethernet Hub